



Flexo FR

Flame Retardant, Economical Sleeving Solution

FLEXO PET FLAME RETARDANT (FR) sleeving is the perfect choice for electronic and high tech applications where flame retardance and durability are primary concerns. Ease of installation makes Flexo FR an efficient choice for long runs of wire or cable.

The addition of an organic combustion inhibitor to our standard polyethylene terephthalate gives Flexo FR an Underwriters Lab and CSA flame resistance rating of VW-1.



- **Approved**
- **Mil-STD 25, FMVSS**
- **Economical Easy Install**
- **Good Abrasion Resistant**
- **Expands to 150%**
- **Halogen Free**
- **Resistant to Gasoline and Engine Chemicals**
- **Temperature Range**
- **°F 94 257°F**
- **Min. 482°F**



Nominal Size	Part #	Expansion Range		Standard Spool Put-Ups		Available Colors	Lbs/100'
		Min.	Max.	Bulk Spool	Shop Spool		
1/8"	FRN0.13	3/32"	1/4"	1,000'	225'	SP, TW, TB & GW	0.16
1/4"	FRN0.25	1/8"	7/16"	1,000'	200'	SP, TW, TB & GW	0.24
3/8"	FRN0.38	3/16"	1/2"	500'	125'	SP, TW, TB & GW	0.57
1/2"	FRN0.50	1/4"	3/4"	500'	100'	SP, TW, TB & GW	0.72
3/4"	FRN0.75	1/2"	1 1/4"	250'	75'	SP, TW, TB & GW	0.87
1"	FRN1.00	5/8"	1 5/8"	250'	65'	SP, TW, TB & GW	1.34
1 1/4"	FRN1.25	3/4"	1 3/4"	250'	50'	SP, TW, TB & GW	1.60
1 1/2"	FRN1.50	1"	2 1/8"	200'	40'	TW, TB & GW	1.96
1 3/4"	FRN1.75	1 1/4"	2 3/4"	200'	30'	SP, TW, TB & GW	2.70
2"	FRN2.00	1 1/2"	3 1/2"	200'	50'	SP, TW, TB & GW	3.30
2 1/2"	FRN2.50	1 3/4"	3 5/8"	200'	50'	SP, TW, TB & GW	3.80
3"	FRN3.00	2 1/2"	4 3/4"	100'	50'	TW, TB & GW	4.00
3 End Construction							
1/4"	FR30.25TB	1/8"	3/8"	1,000'	200'	TB	0.39

